



Unit: mm

Bolt		Type		Inside Diameter	Outside Diameter	Thickness	Material		
Size	Thread	Flat - DIN125					D1	D2	H
		Form A	Form B						
1.7	M1.6	WF-D125A	WF-D125B	1.7 - 1.84	3.7 - 4.0	0.25 - 0.35	SS	304/A2/18-8 Stainless Steel	
1.8	M1.7			1.8 - 1.94	4.2 - 4.5	0.25 - 0.35			
2.2	M2			2.2 - 2.34	4.7 - 5.0	0.25 - 0.35	SCR	316/A4 Stainless Steel	
2.5	M2.3			2.5 - 2.64	5.7 - 6.0	0.45 - 0.55			
2.7	M2.5			2.7 - 2.84	5.7 - 6.0	0.45 - 0.55	BOS	Black Oxide Steel	
2.8	M2.6			2.8 - 2.94	6.64 - 7.0	0.45 - 0.55			
3.2	M3			3.2 - 3.38	6.64 - 7.0	0.45 - 0.55	ZI	Zinc Plated Steel	
3.7	M3.5			3.7 - 3.88	7.64 - 8.0	0.45 - 0.55			
4.3	M4			4.3 - 4.48	8.64 - 9.0	0.7 - 0.9			
5.3	M5			5.3 - 5.48	9.64 - 10.0	0.9 - 1.1			
6.4	M6			6.4 - 6.62	11.57 - 12.0	1.4 - 1.8			
7.4	M7			7.4 - 7.62	13.57 - 14.0	1.4 - 1.8			
8.4	M8			8.4 - 8.62	15.57 - 16.0	1.4 - 1.8			
11	M10			10.5 - 10.77	19.48 - 20.0	1.8 - 2.2			
12	M12			13.0 - 13.27	23.48 - 24.0	2.3 - 2.7			
15	M14			15.0 - 15.27	27.48 - 28.0	2.3 - 2.7			
17	M16			17.0 - 17.27	29.48 - 30.0	2.7 - 3.3			

VXA010624