



<b>W</b>	<b>WASHER</b>	<b>Part Number Designation</b>			
		<b>WTL-D6798A</b>	<b>- M3</b>	<b>- ZI</b>	
<b>WTL-D6798</b>	<b>WASHER - TOOTH LOCK- DIN6798</b>	↓ Type	↓ Bolt Thread	↓ Material	
<b>Metric DIN6798 Tooth/Serrated Lock Washer</b>		<b>WTL-D6798A</b>		<b>WTL-D6798J</b>	
			h=3S		h=3S

Unit: mm

Bolt		Type		Inside Diameter (D1)	Outside Diameter (D2)	Tooth Thickness Only ref (S)	Teeth min		Material			
		Tooth/Serrated Lock					A	J	Symbol	Stand for		
Size	Thread	DIN6798A	DIN6798J									
1.7	M1.6	<b>WTL-D6798A</b>	<b>WTL-D6798J</b>	1.7 - 1.84	3.3 - 3.6	0.3	9	7	SS	304/A2/18-8 Stainless Steel		
2.2	M2			2.2 - 2.34	4.2 - 4.5	0.3	9	7				
2.7	M2.5			2.7 - 2.84	5.2 - 5.5	0.4	9	7	SCR	316/A4 Stainless Steel		
3.2	M3			3.2 - 3.38	5.7 - 6.0	0.4	9	7				
3.7	M3.5			3.7 - 5.48	6.64 - 7.0	0.5	10	7	ZI	Zinc Plated Steel		
4.3	M4			4.3 - 4.48	7.64 - 8.0	0.5	11	8				
5.3	M5			5.3 - 5.48	9.64 - 10.0	0.6	11	8				
6.4	M6			6.4 - 6.62	10.57 - 11.0	0.7	12	9				
7.4	M7			7.4 - 7.62	12.07 - 12.05	0.8	14	10				
8.4	M8			8.4 - 8.62	14.07 - 15.0	0.8	14	10				
11	M10			10.5 - 10.77	17.57 - 18.0	0.9	16	12				
13	M12			13.0 - 13.27	19.98 - 20.5	1.0	16	12				
15	M14			15.0 - 15.27	25.48 - 24.0	1.0	18	14			<b>VXA010624</b>	
17	M16			17.0 - 17.27	25.48 - 26.0	1.2	18	14				