



NTF	Insert Nut	Part Number Designation				
		NTF ↓ Type	-	M2 ↓ Thread Code	-	1 ↓ Shank Code
						

Unit: mm

METRIC	Thread Size	Type		Thread Code	Shank Code	A (Shank) Max.	Rec. Min. Sheet Thickness	Hole Size in Sheet +0.08	C Max.	H Nom.	Min. Dist. HoleC/L To Edge
		Fastener Material									
		Stainless	Hardened								
M2x0.4	S30	S40	M2	1	1.53	1.53-2.3	4.37	4.35	4.8	6	
				2	2.3	2.32 Min					
M2.5x0.45	S30	S40	M2.5	1	1.53	1.53-2.3	4.37	4.35	4.8	6	
				2	2.3	2.32 Min					
M3x0.5	S30	S40	M3	1	1.53	1.53-2.3	4.37	4.35	4.8	6	
				2	2.3	2.32 Min					
M4x0.7	S30	S40	M4	1	1.53	1.53-2.3	7.37	7.35	7.9	7.2	
				2	2.3	2.32 Min					
M5x0.8	S30	S40	M5	1	1.53	1.53-2.3	7.92	7.9	8.7	8	
				2	2.3	2.32 Min					
M6x1	S30	S40	M6	3	3.05	3.18-3.94	8.74	8.72	9.5	8.8	
				4	3.84	3.96-4.72					
				5	4.63	4.75 Min					

Unit: inch

INCH	Thread Size	Type		Thread Code	Shank Code	A (Shank) Max.	Rec. Min. Sheet Thickness	Hole Size in Sheet +0.08	C Max.	H Nom.	Min. Dist. HoleC/L To Edge
		Fastener Material									
		Stainless	Hardened								
.865-56 (#2-56)	S30	S40	256	1	.060	.060-0.90	.172	.171	.188	.23	
				2	.090	.091 Min					
.112-40 (#4-40)	S30	S40	440	1	.060	.060-0.90	.172	.171	.188	.23	
				2	.090	.091 Min					
.138-32 (#6-32)	S30	S40	632	1	.060	.060-0.90	.213	.212	.250	.27	
				2	.090	.091 Min					
.164-32 (#8-32)	S30	S40	832	1	.060	.060-0.90	.290	.289	.312	.28	
				2	.090	.091 Min					
.190-32 (#10-32)	S30	S40	032	1	.060	.060-0.90	.312	.311	.343	.31	
				2	.090	.091 Min					
.250-20 (1/4-20)	S30	S40	0420	3	.120	.125-.155	.344	.343	.375	.34	