



BDO	Blind Threaded Standoffs	Part Number Designation						
		BDO	-	M3	-	6	-	S
		Type	Thread Code		Length Code		Material	
								

Unit: mm

METRIC	Thread Size x Pitch	Type				Thread Code	"L" ±0.05-0.13 (Length Code in millimeters)										Min Sheet Thick-ness	Hole Size In Sheet +0.08 -.000	C -0.13	H Nom.	Min. Dist. Hole C/L To Edge
		Steel	Stainless Steel	Alu-minum	Hardened Stainless Steel																
	M3 x 0.5	S	S30	AL	S40	M3	6	8	10	12	14	16	18	20	22	25	1	4.22	4.18	4.75	6
						3.5M3											1	5.41	5.38	6.35	7.1
	M4 x 0.7	S	S30	AL	S40	3.5M4	6	8	10	12	14	16	18	20	22	25	1.30	6.00	5.98	7.0	7.5
						M4											1.30	7.20	7.12	8.0	8.4
	M5 x0.8	S	S30	AL	S40	M5	6	8	10	12	14	16	18	20	22	25	1.30	7.20	7.12	8.0	8.4
	M6 x 1.0	S	S30	AL	S40	M6	6	8	10	12	14	16	18	20	22	25	1.30	8.75	8.72	10	13

Unit: inch

INCH	Thread Size x Pitch	Type				Thread Code	"L"+0.002-0.005 (Length Code in 32nds of an inch)																Min Sheet Thick-ness	Hole Size In Sheet +0.03 -0.000	C +.000 -0.005	H Nom.	Min. Dist. Hole C/L To Edge
		Steel	Stainless Steel	Alu-minum	Hardened Stainless Steel																						
							.312	.375	.437	.500	.562	.625	.687	.750	.812	.875	.937	1.00	1.062								
	.112-40 (#4-40)	ZI	S30	AL	S40	440	10	12	14	16	18	20	22	24	26	28	30	32	34	.040	.166	.165	.187	.23			
						6440														.040	.213	.212	.250	.27			
	.138-32 (#6-32)	ZI	S30	AL	S40	632	10	12	14	16	18	20	22	24	26	28	30	32	34	.040	.213	.212	.250	.27			
8632						.050														.281	.280	.312	.31				
.164-32 (#8-32)	ZI	S30	AL	S40	832	10	12	14	16	18	20	22	24	26	28	30	32	34	.050	.281	.280	.312	.31				
.190-32 (#10-32)	ZI	S30	AL	S40	032	10	12	14	16	18	20	22	24	26	28	30	32	34	.050	.281	.280	.312	.31				